PRODUCT FICHE

Complying Commission Delegated Regulation (EU) No 392/2012

Complying Commission Delegated Regula	tion (EU) No 392/2	2012
Supplier name or trademark		Beko
Model name		DCUR801S
Rated capacity (kg)		
		8
Type of Tumble Dryer	Air Vented	No.
Energy efficiency class (1)	Condenser	
		В
Annual Energy Consumption (kWh) (2)		561
Type of Control	Automatic	•
	Non-Automatic	-
Energy consumption of the standard cotton programme at full	load (kWh)	4,71
Energy consumption of the standard cotton programme at part		2,54
Power consumption of the left-on mode for the standart cotton programme at full load, PL (W) Power consumption of the off-mode for the standart cotton programme at full load, PO (W)		0,3
		1
The duration of the left on mode (min)		
Standard cotton programme (3)		
Programme time of the standard cotton programme at full load,	Tdry (min)	137
Programme time of the standard cotton programme at partial lo (min)		78
Weighted programme time of the standard cotton programme a		70
partial load (11)	t full and	103
Condensation efficiency class (4)		В
Average condensation efficiency of the standard cotton program	me at partial	
load, Cary		%89
Average condensation efficiency of the standard cotton program load, Cdry1/2		%89
Weighted condensation efficiency of the standard cotton program load and partial load, Ct	mme at full	89%
Sound power level for the standard cotton programme at full load	d (5)	66
Built-in Yes • No -		_

⁽¹⁾ Scale from A+++ (most efficient) to D (least efficient)

⁽²⁾ Energy consumption based on 160 drying cycles of the standard cotton programme at full and partial load, and the consumption of the low-power modes. Actual energy consumption per cycle will depend on how the appliance is used.

^{(3) &}quot;Cotton cupboard dry programme" used at full and partial load is the standard drying programme to which the information in the label and the fiche relates, that this programme is suitable for drying normal wet cotton laundry and that it is the most efficient programme in terms of

⁽⁴⁾ Scale from G (lest efficient) to A (most efficient)

⁽⁵⁾ Weighted average value — LWA expressed in dB(A) re 1 pW