

PRODUCT FICHE	
Energy Label Directive EU2010/30/EU-No65/2014 of range hoods	
Brand	GRUNDIG
Model	GDI 5795 BX
Annual Energy Consumption(AEC hood)(kWh/a)	27,7
Energy Efficiency Class	A
Fluid Dynamic Efficiency (FDE hood)	30,7
Fluid Dynamic Efficiency Class	A
Lighting Efficiency (LE hood) (lux/watt)	53
Lighting Efficiency Class	A
Grease Filtering Efficiency	87,7
Grease Filtering Efficiency Class	B
Air flow (m³/h) (min. and max. setting)	240-500
Air flow (m³/h) (boost setting)	750
Sound power level (dB) (min. and max. setting)	45-57
Sound power level (dB) (boost setting)	65
Measured power consumption in standby mode (Ps) (W)	0,42
Measured power consumption off mode (Po)(W)	0,42

INSTRUCTION BOOKLET	
Information for domestic range hoods	
Comply with EU directive 2009/125/EC Regulation No 66/2014	
Brand	GRUNDIG
Model	GDI 5795 BX
Annual Energy Consumption(AEC hood)(kWh/a)	27,7
Time increase factor (f)	0,9
Fluid Dynamic Efficiency (FDE hood)	30,7
Energy Efficiency Index (EEI hood)	46,8
Measured air flow rate at best efficiency point (QBEP) (m³/h)	300,7
Measured air pressure at best efficiency point (PBEP) (Pa)	278
Maximum air flow (Q max) (m³/h)	750
Measured electric power input at best efficiency point(WBEP) (W)	75,7
Nominal power of the lighting system (WL)(W)	4
Average illumination of the lighting system on the cooking surface (E middle)(lux)	212
Measured power consumption in standby mode (Ps) (W)	0,42
Measured power consumption off mode (Po)(W)	0,42
Sound power level (LWA)(dB)	57